



Króciec Geberit Mapress C-Stahl, ocynkowany zewnętrznie



Ilustracja przykładowa

CHARAKTERYSTYKA

- Ocynkowany zewnętrznie

DANE TECHNICZNE

Materiał

Stal niestopowa 1.0034 E195
(EN 10305)

| Nr art. | DN | d _o mm | d _i mm | s mm | L cm |
|---------|----|-------------------|-------------------|------|------|
| 22050 | 12 | 15 | 12.6 | 1.2 | 5 |
| 22051 | 15 | 18 | 15.6 | 1.2 | 5 |
| 22052 | 20 | 22 | 19 | 1.5 | 5.2 |
| 22053 | 25 | 28 | 25 | 1.5 | 5.6 |
| 22054 | 32 | 35 | 32 | 1.5 | 6.2 |
| 22055 | 40 | 42 | 39 | 1.5 | 8 |
| 22056 | 50 | 54 | 51 | 1.5 | 9 |

| <i>Nr art.</i> | <i>DN</i> | <i>d_g</i> <i>mm</i> | <i>d_i</i> <i>mm</i> | <i>s</i> <i>mm</i> | <i>L</i> <i>cm</i> |
|----------------|-----------|-----------------------------------|-----------------------------------|-----------------------|-----------------------|
| 22057 | 65 | 76.1 | 72.1 | 2 | 13.6 |
| 22058 | 80 | 88.9 | 84.9 | 2 | 15 |
| 22059 | 100 | 108 | 104 | 2 | 18 |