


**A114**

**A115**

### Description

Four way squared body auxiliary inlet connection, used to supplement the fire protection water supply. Bodies do not have clappers. Clapper snoots (A91C), are required when they are used as Fire Department inlet connection. Another function is as test header (Flush Fire Dept.). Every fire pump needs a method of testing to verify it is functioning properly. One of the more common methods is the use of a test header arrangement. A test header allows for the flowing of large quantities of water through multiple hoses.

### Versions and product codes

Series	Size	Type	Finishing
<b>A114</b> BACK OUTLET BODY	6" x 3"	NPT inlets (F) x NPT outlet (F)	Rough bronze
	8" x 3"		
<b>A115</b> ANGLE OUTLET BODY	6" x 3"	NPT inlets (F) x NPT outlet (F)	Rough bronze
	8" x 3"		



**Note.**  
The 8" versions use the 6" bodies with an adapter 6" x 8".

### Technical data


- Rated pressure: 300 PSI (20,6 bar)

### Materials


- Body: casted Bronze CB491K UNI EN1982-2000
- Tensile strength of the material in the shape of bar: min. 220 MPa
- Stress for permanent distortion R(0.2): min. 110 MPa
- Elongation: min. 6 %

### Dimensions

#### A114 – BACK OUTLET BODY, NPT (F x F)



#### A115 - ANGLE OUTLET BODY, NPT (F x F)



### Product specifications

#### A114 – BACK OUTLET BODY 6"

Flush Fire Department inlet connection clapper snoot type (body does not include clappers), back outlet body, NPT (F x F), with main feature as following:

- Casted bronze
- 6" female NPT outlet
- 3" female NPT inlets
- Rated pressure 300 psi

#### A114 – BACK OUTLET BODY 8"

Flush Fire Department inlet connection clapper snoot type (body does not include clappers), back outlet body, NPT (F x F), with main feature as following:

- Casted bronze
- 8" female NPT outlet
- 3" female NPT inlets
- Rated pressure 300 psi

FLUSH FIRE DEPARTMENT INLET CONNECTIONS CLAPPER  
SNOOT TYPE  
**A114 AND A115 SERIES**



**GIACOMINI**  
WATER E-MOTION

**A115 - ANGLE OUTLET BODY 6"**


Flush Fire Department inlet connection clapper snoot type (body does not include clappers), angle outlet body, NPT (F x F), with main feature as following:

- Casted bronze
- 6" female NPT outlet
- 3" female NPT inlets
- Rated pressure 300 psi

**A115 - ANGLE OUTLET BODY 8"**

Flush Fire Department inlet connection clapper snoot type (body does not include clappers), angle outlet body, NPT (F x F), with main feature as following:

- Casted bronze
- 8" female NPT outlet
- 3" female NPT inlets
- Rated pressure 300 psi

**Additional information**

For additional information please check the website [www.giacomini.com](http://www.giacomini.com) or contact the technical service: ☎ +39 0322 923372 📠 +39 0322 923255 ✉ [consulenza.prodotti@giacomini.com](mailto:consulenza.prodotti@giacomini.com)  
This pamphlet is merely for information purposes. Giacomini S.p.A. retains the right to make modifications for technical or commercial reasons, without prior notice, to the items described in this pamphlet. The information described in this technical pamphlet does not exempt the user from following carefully the existing regulations and norms on good workmanship.  
Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy